

SAMMYS®
SPEEDY
CLAMP



CHANGING THE
BEAM CLAMP GAME



Sammys® Speedy Clamp is engineered to eliminate manual steps, reduce installation time, and support consistently reliable and compliant installations at a distance.

4 STEPS ARE 3 TOO MANY

STOP INSTALLING THE HARD WAY

Manual **four-step** beam clamp installs take time and increase risk of user error. Limited attachment point access due to existing obstructions often leads to workarounds that compromise safety and compliance.

Manual Install: ■ ■ ■ ■ FOUR STEPS
Speedy Clamp: ■ ONE STEP

THERE'S A BETTER WAY.
ONE POWER-TOOL-DRIVEN STEP.
ZERO GUESSWORK.
CONSISTENT, OPTIMAL
CLAMPING EVERY TIME—
FROM A DISTANCE.

4X

Up to 4x faster installs



Our patented tightening technology ensures proper and consistent clamping force.



Improved safety and compliance for installations at a distance, no ladder required.

DESIGNED FOR VOLUME. BUILT FOR HARD-TO-REACH INSTALLS

HIGH-VOLUME JOBS

For large-scale, repetitive installs where every second counts.



Faster Installs: Reduces labor across high-volume projects.



Consistent Results: Delivers consistent clamping force across all installer experience levels.



Reduced Fatigue: Eliminates the repetitive pain of manual wrenching all day long.

(Data Centers, warehouses, manufacturing)

RETROFIT & REMODEL SPECIALISTS

For overhead obstructions and hard-to-reach installation points.



Reduced Risk: Eliminates ladders and dangerous workarounds when attachment points are inaccessible.



No Ladder Required: Saves significant time by eliminating continuous climbing throughout the day.



Compliant Installs: Ensures the jam nut is properly tightened and the threaded rod is installed correctly without improper workarounds.

NO ACCESS? NO PROBLEM.

REALIZE SPEED AND SAFETY BENEFITS FROM A DISTANCE

With our extension installation kit, beam clamp installation from a distance has never been easier in retrofit and service environments.



Use with a standard
1/4" impact driver.



**SCAN TO WATCH
INSTALLATION VIDEO**

	Approvals	Part No.	Model	Description	Coating	Threaded Rod Size	Max Rec. Load Top Flange	Max Rec. Load Bottom Flange	Set Screw Size	Max UL Pipe Size	Box Qty
		8905000	SSC 38	3/8" Plain Speedy Clamp	Plain	3/8"-16	500lbs	250lbs	3/8"-16	4" NPS	50
		8906000	SSC 38Z	3/8" Zinc Speedy Clamp	Zinc	3/8"-16	500lbs	250lbs	3/8"-16	4" NPS	50

Includes swivel socket
and threaded rod holder
to optimize precise
installations.

Enables installations at
a distance with adapters
that fit to any length of
3/4" EMT.

Part No.	Model	Description	Box Qty
8801000	SCT 100	1 x Sammys Speedy Clamp Installation Tool	1
8800000	SCKIT 100	1 x Sammys Speedy Clamp Installation Tool with Extension Kit	1



www.sammysanchors.com

IMPORTANT: Do NOT use a power tool to reinstall or reuse the Speedy Clamp.

©2026 Illinois Tool Works, Inc.