

SAMMY**X****PRESS**

Drill/Drive™

NEW!

THE FASTEST WAY TO ATTACH THREADED ROD TO LIGHT GAUGE STEEL JUST GOT FASTER

**SIMPLIFY YOUR WORKFLOW AND SIGNIFICANTLY REDUCE
INSTALLATION TIME WITH THE BUILT-IN DRILL POINT. SAY
GOODBYE TO THE HASSLE OF REPLACEMENT DRILL BITS.**

- **NO MORE** LOST DRILL BITS
- **NO MORE** DULL BIT TIPS
- **NO MORE** MULTI-STEP INSTALLATION

**SAVE TIME ON
JOBS WITH OUR
UNIVERSAL
INSTALL TOOL**

SAMMY
XPRESS It™ 2.0

Part No. 8196910



Insert and lock in
X-Press Drill/Drive anchor



Drill the hole using the
self-drilling tip



Install by expanding
the anchor

SAMMYS®
THREADED ROD ANCHORING SYSTEM

WWW.SAMMYSANCHORS.COM



DRILL/DRIVE

Approvals	Rod Size	Part Number	Model	Description	Ultimate Pullout (lbs)	UL Load Rating (lbs)	UL Min Thick	Max. Thick	Box Qty	Case Qty	Application
	3/8"	8151957	XPDD 40	Sammy X-Press Drill/Drive 40	1092 (22 ga.) 1340 (20 ga.) 1733 (16 ga.)	850 (2-1/2" Pipe) (22 ga.) 1500 (4" Pipe) (16 ga.) 185 (22 ga. Luminaire) 250 (20 ga. Luminaire) 283 (22 ga. Conduit & Cable) 500 (16 ga. Conduit & Cable)	22 ga. 16 ga. 22 ga. 20 ga. 22 ga. 16 ga.	1/8"	25	125	Metal Deck/Purlin

ADDITIONAL SAMMY X-PRESS MODELS:


VERTICAL MOUNT

Approvals	Rod Size	Part Number	Model	Description	Ultimate Pullout (lbs)	UL Load Rating (lbs)	UL Min Thick	FM Test Load (lbs)	FM Min Thick	Max. Thick	Box Qty	Case Qty	Application
	1/4"	8181922	XP 200	Sammy X-Press 200	1146 (22 ga.)	185 (Luminaire) 250 (Luminaire)	22 ga. 16 ga.			1/8"	25	125	Metal Deck/Purlin
	3/8"	8150922	XP 20	Sammy X-Press 20	1146 (22 ga.)	850 (2 1/2" Pipe) 185 (Luminaire) 250 (Luminaire) 283 (Conduit & Cable)	22 ga. 22 ga. 16 ga. 22 ga.	940 (2" Pipe) 1475 (4" Pipe)	22 ga. 12 ga.	1/8"	25	125	Metal Deck/Purlin
	3/8"	8150922	XP 20	Sammy X-Press 20	1146 (22 ga.)	850 (2 1/2" Pipe)	22 ga.	Pre-Pour Structural Concrete @ 3000 psi Post-Pour Range II LWC ≤ 35 PCF (lbs/ft³)			25	125	Metal Deck (Pre-Pour & Post-Pour)/Purlin
	3/8"	8153922	XP 35	Sammy X-Press 35	1783 (16 ga.)	1500 (4" Pipe) 185 (Luminaire) 250 (Luminaire) 416 (Conduit & Cable)	16 ga. 22 ga. 16 ga. 16 ga.	940 (2" Pipe) 1475 (4" Pipe)	22 ga. 12 ga.	1/8"	25	125	Metal Deck/Purlin

Pre-Pour Structural Concrete @ 3000 psi



Post-Pour Range II
LWC ≤ 35 PCF (lbs/ft³)



HORIZONTAL MOUNT

Approvals	Rod Size	Part Number	Model	Description	Ultimate Shear (lbs)	UL Load Rating (lbs)	UL Min Thick	Max. Thick	Box Qty	Case Qty	Application
	3/8"	8293957	SWXP35	Sidewinder X-Press 35	1798 (16 ga.)	1250 (3 1/2" Pipe) 80 (Luminaire) 416 (Conduit & Cable)	16 ga.	1/8"	25	125	Metal Deck/Purlin

SWIVEL MOUNT

Approvals	Rod Size	Part Number	Model	Description	Ultimate Pullout (lbs)	UL Load Rating (lbs)	UL Min Thick	FM Test Load (lbs)	FM Min Thick	Max. Thick	Box Qty	Case Qty	Application
	3/8"	8294922	SXP 20	Swivel X-Press 20	1061 (22 ga Vert) 829 (45° Off Vert)	750 (2" Pipe) 170 Vertical (Luminaire) 80 @ 45° (Luminaire) 283 Vertical (Conduit & Cable) 233 @ 45° (Conduit & Cable)	22 ga.	635 (2" Pipe)	22 ga.	1/8"	25	125	Metal Deck/Purlin
	3/8"	8295922	SXP 35	Swivel X-Press 35	1675 (16 ga Vert) 1558 (89° Off Vert)	1250 (3 1/2" Pipe) 250 Vertical (Luminaire) 80 @ 90° (Luminaire) 500 Vertical (Conduit & Cable) 333 @ 89° (Conduit & Cable)	16 ga.	635 (2" Pipe)	22 ga.	1/8"	25	125	Metal Deck/Purlin
†	1/2"	8272957	SXP 2.0	Swivel X-Press 2.0	1061 (22 ga Vert) 829 (45° Off Vert)					1/8"	25	125	Metal Deck/Purlin
†	1/2"	8271957	SXP 3.5	Swivel X-Press 3.5	1675 (16 ga Vert) 1558 (89° Off Vert)					1/8"	25	125	Metal Deck/Purlin

† Approved for Sway Bar Bracing Only

SHEET STEEL GAUGES

Gauge Number	26	24	22	20	18	16	14	12
Decimal Equivalent	.018"	.024"	.030"	.036"	.048"	.060"	.075"	.105"

The values listed are ultimate averages under laboratory conditions and apply to Buildex manufactured fasteners only. Appropriate safety factors should be applied to these values for design purposes.



ASSEMBLED IN THE U.S.A.



Visit www.sammysanchors.com for additional approval information.



Scan for
installation
instructions

SAMMYS®
THREADED ROD ANCHORING SYSTEM

WWW.SAMMYSANCHORS.COM